



## MANNOL Turbine 68 2303

High-quality turbine (circulating) oil with an increased replacement age designed for the lubrication and cooling of bearings in stationary steam and water turbines at normal and elevated temperatures and manufactured on a highly-purified base.

Properties properties:

- A modern additives package combined with a highest-quality mineral base with an optimal viscosity in a wide range of temperatures ensure excellent antifriction, antiwear and anti-scuffing properties that significantly extend the expected life of the equipment in all even most extreme operation modes in a wide range of ambient temperatures and ensure a significant extension of the expected life of the equipment;
- It has a great ability of a heat removal from the bearing system thus extending the service life of bearings;
- They are characteristic of a highest resistance to oxidation even at high temperatures and, as a result, of an increased resistance to ageing during long operation, which allows preserving operating properties throughout the entire period between replacements thus reducing turbine maintenance costs;
- They are characteristic of a low tendency towards the formation of deposits which minimises the formation of lacquers on friction type bearings and reduces the possibility of an unplanned equipment shutdown;
- They have exceptional anticorrosion properties even at the presence of water/vapours and condensate, which reduces spare parts buying costs;
- A high hydrolytic stability, a reliable water segregation (including vapours with the condensed water exudation) prevent the formation of stable emulsions thus preserving the operating efficiency of the lubrication system and extending the expected life of the equipment;
- A quick deaeration (air separation) ensures the lubrication film stability, extends the expected life of the equipment;
- A low foam formation ensures the continuity of the oil supply into fraction subsystems that reduces the possibility of overheating;
- An excellent filtering ability reduces maintenance costs of the technical equipment;
- They ensure a replacement age not less than 5,000 hours.

They were designed for steam and water turbines as well as various hydraulic industrial circulating systems. They may be used for axial-flow and radial turbo compressors and water pumps, turbine hydraulic control systems. They may be used in gas turbines if oils of such grade are indicated in the user's manual of the equipment.

In order to properly use them, thoroughly read the user's manual of the equipment!

ISO Viscosity Grade 68  
DIN 51524-1  
DIN 51524-2  
DIN 51524-3  
DIN 51517-2  
DIN 51506 (VBL  
DIN VCL  
DIN VDL)  
DIN 51515-1 (L-TD)  
DIN 51515-2 (TG)  
ISO DP 6521 (DAA  
ISO DP DAB  
ISO DP DAH  
ISO DP DAG)  
AFNOR FRANCE NF E 48-603  
BSI GB BS 489  
CEGB 207001  
MIL L 17672 D  
VDMA 24568  
BROWN BOVERI HTGD 90117  
GE GEK 32568 A/GEK 32568 C  
MAG CINCINNATI P-38  
MAG CINCINNATI P-55  
MAG CINCINNATI P-54  
MAG CINCINNATI P-57  
MAG CINCINNATI P-62  
MITSUBISHI E00-87182  
PARKER DENISON HF-0  
SIEMENS TLV 9013  
US STEEL 120

## PACKAGING

208L	MN2303-DR	Drum
1000L	MN2303-IBC	Pallet tank