



ATF Exchanger (PNEU) CT4112

Product Features:

- Exclusive Deeptrans technology enhances fluid exchange performance by 50%.
- Patented Double Wall Tank design let new fluid become warm which gives protection to transmission and pipelines.
- The high precision scale marks allows more accurate result of calibration and transfer rate. Precise manual transfer rate is guaranteed, if necessary.
- One-button control to complete processes like new/waste fluid exchanging, - quick and convenient.
- Available to check real-time changing results via two sight glasses
- Vehicle database included and can be updated through USB port.
- Two fluid refill options
- Standard adapters work for most cars. Optional 72 types of adapter are available for special needs.
- Premium swivel casters with ideal-stop brake.

Technical data:

Voltage: AC220V 50/60Hz 1Ph

Power - 140W

Pressure gauge range 0~16Bar(0~220Psi)

Operating pressure 6Bar(0~87Psi)

Length of oil outlet hose - 2.5m

Length of oil return hose - 2.5m

Length of oil drain hose - 2.0m

Filter element precision - 5µm

Volume of new oil tank 19.5L

Volume of waste oil tank 15.5L

Equivalent replacement error ±0.05L

Oil speed of oil exchange - 3.0L /Min

Dimension of machine: 510mm x 485mm x 1360mm

Package dimension: 495mm x 495mm x 1390mm